HIGH-FROUDE HULL SHIP

CLAIM OF PRIORITY

[1]   This application claims priority from U.S. Provisional Application Serial No. 60/426,070, which was filed on November 12, 2002, which is incorporated by reference.

BACKGROUND OF THE INVENTION

5   [2]   The shape of a typical ship's hull is designed to minimize the drag of the water on the ship such that it travels on the surface of the water as efficiently as possible. This can be seen in the vast majority of large-waterplane-area ship's today in their long and sleek look. A large-waterplane-area ship, which garners the majority of its buoyancy from the amount of surface area of the hull that meets the plane of water, can be

10   distinguished from a small waterplane area ship, which garners the majority of its buoyancy from underwater displacement pontoons. The long and narrow hull of a large-waterplane-area ship minimizes the effects of the water on the acceleration and velocity of the ship. As a general rule, the longer the length of the hull is with respect to its width, the more efficient the vessel operates.

15   [3]   Several physical factors affect the operation of both small and large-waterplane-area ships. For example, strong headwinds or other wind resistance will affect the velocity and acceleration of a ship. In another example, the friction of the water against the ship constantly works against the velocity of the ship. Another physical factor, discussed in greater depth below, is the wave drag of a ship. That is, the effect of the

20   ship's own wake working against its velocity.

1

[4] It is well known in the art that a Froude number may be used to mathematically express the efficiency of the ship's hull design with respect to wave drag. The ship's Froude number is defined as follows:

$$F = v/sqrt(g*l),$$

5   v = velocity ,

g = acceleration of gravity, and

l = length of hull.

[5] The effect of wave drag on a ship's velocity is described in Modern Ship Design, by Thomas C. Gillmer, 1970 which states, "The practical limiting speed for displacement

10   surface vessels is basically that of wavelength to ship length, where one wavelength, created by the ship, is equal to the ship's waterline length." For efficient operation from the standpoint of powering and fuel consumption, typical ships have a velocity limit corresponding to a Froude number of 0.4. When a ship attempts to exceed this velocity limit, the drag of the water increases exponentially and the resulting power required to

15   overcome the additional drag leads to extreme inefficiency. As a result, a ship is not typically designed with such propulsion requirements in mind.

[6] **FIG. 1** is a graph of a typical ship's wave drag (Cw) versus its Froude number. As can be seen, at low Froude numbers the wave drag is relatively low, proportionally increasing as the Froude number increases. An increase in the Froude number

20   represents an increase in the velocity of the ship which corresponds to an increase in wave drag Cw. However, when the ship's velocity reaches the point corresponding to a Froude number of 0.4, the wave drag Cw increases exponentially with respect to an increase in the ship's velocity. This increase in wave drag Cw is well established in the prior art for all surface displacement ships and is often referred to as the resistance or

2

powering "hump" *100*. A hull experiences peak wave drag Cw in the center of the hump *100*, which corresponds to a Froude number of 0.5.

[7] Because of the high wave drag Cw, operation in the hump *100* region requires high propulsion power which leads to inefficient fuel usage. A ship that requires a constant operational velocity for a long time should not do so in the hump *100* region. As a result, the overall length of a ship's hull designed today is typically increased to allow the ship to reach greater velocities before the Froude number reaches 0.4. That is, most large-waterplane-area ships are designed to operate below the hump *100*.

[8] For example, **FIG. 2** is a plan view of a conventional ship *200* having a relatively large overall hull length *205* as compared to its width W. The ship *200* is designed to operate at velocities corresponding to Froude numbers less than 0.4. If greater velocities are desired, one can design the ship's hull to be longer such that the 0.4 Froude number corresponds to a higher velocity than before. The alternative is to provide enough propulsion power to overcome the hump *100*, such as with modern Destroyers or other high speed ships. Both solutions are inefficient because space is wasted by either increasing the length of the hull or the amount of propulsion power. As a result, it is difficult to efficiently gain velocity beyond a Froude number of 0.4 in large-waterplane-area ships.

[9] It is also known in the art that operating a ship at a velocity having a corresponding Froude number greater than 0.8 substantially reduces wave drag Cw. Again referring to **FIG. 1**, one can see that the amount of wave drag Cw is substantially the same at a Froude number of 0.8 as it is for a Froude number of 0.4. That is, once the velocity of the ship overcomes the high wave drag Cw of the hump *100*, additional increases in velocity do not require an exponential increase in propulsion power.

3

[10] One such ship designed to operate at velocities corresponding to Froude numbers greater than 0.8 is disclosed in U.S. Patent No. 5,592,895, entitled SMALL WATERPLANE AREA HIGH SPEED SHIP to Schmidt, which is assigned to the Lockheed Missiles and Space Co. and which is incorporated by reference. In this

5 disclosure, Schmidt describes a small waterplane ship designed to operate at high speeds corresponding to Froude numbers greater than 0.8. Specifically, Schmidt disregards the convention of designing a hull to be as long as possible to attain greater velocities before the Froude number reaches 0.4 by disclosing a ship with a short hull wherein the hump 100 is overcome at fairly low velocities. The short hull, however,

10 limits the size of the ship and the concept is not practicable for large-waterplane-area ships that require substantial payload capabilities.

[11] Therefore, it is desirable to have a large-waterplane-area ship that reaches and surpasses the hump *100* at a low velocity such that the ship's operational velocity or cruising velocity is above the hump *100* at a high Froude number while also having a

15 hull that provides substantial payload capacity.

SUMMARY OF THE INVENTION

[12] An embodiment of the invention is directed to a large-waterplane-area ship

20 operable to efficiently operate at a high-Froude velocity. In one embodiment, a large-waterplane-area ship includes a hull structure having a plurality of exclusive hull portions protruding from a main body of the hull structure. Each hull portion has a length shorter than the length of the main body and each hull portion has a buoyancy wherein the combined buoyancy of each hull portion is sufficient to support the main body above a

4

waterline. As such, each hull portion acts independently and exclusively of other hull portions with respect to the effects of wave drag. Therefore, the ship overcomes the wave drag at lower velocities while also having a relatively long main body.

[13]   In another embodiment, a large-waterplane-area ship includes a plurality of struts protruding from a main body and a plurality of pontoons each coupled to at least one of the plurality of struts. The buoyancy of the pontoons can be adjusted such that the ship operates as a large-waterplane-area ship with multiple hull portions allowing velocities in the high-Froude area or adjusted such that the ship operates as a small waterplane-area ship with multiple submerged pontoons providing buoyancy while still allowing velocities in the high-Froude area.

BRIEF DESCRIPTION OF THE DRAWINGS

[14]   The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings.

[15]   FIG. 1 is a graph of a typical ship's wave drag (Cw) versus its Froude number.

[16]   FIG. 2 is a plan view of a conventional ship having a relatively large overall hull length as compared to its width.

[17]   FIG. 3 is a plan view of a ship having a plurality of hull portions according to an embodiment of the invention.

[18]   FIG. 4 is a plan view of another ship having a plurality of hull portions according to another embodiment of the invention.

5

[19] **FIG. 5** is an isometric view of another ship having a plurality of exclusive hull portions according to another embodiment of the invention.

DETAILED DESCRIPTION

5 **[20]** **FIG. 3** is a plan view of a ship *300* having a plurality of exclusive hull portions *301a-d* according to an embodiment of the invention. In this embodiment, the ship *300* has four hull portions *301a-d* that protrude from a main hull structure or frame *310.* The hull portions *301a-d* each have a length X, where X is less than a length L of the Frame *310* which provide a combined buoyancy that support the ship *300* in water. That is,

10 each hull portion *301a-d* has a buoyancy that when combined with the buoyancies of the other hull portions is enough to support the weight of the ship *300* above a waterline *350* such that the frame *310* does not engage the waterline *350.* Since the Frame *310* does not engage the waterline *350*, the frame does not add buoyancy to support to the ship *300*.

15 **[21]** Because the combined buoyancy of the hull portions *301a-d* supports the ship *300* with its frame *310* above the waterline *350*, the hull portions *301a-d* are exclusive of one another with respect to determining wave drag as a function of velocity. Each hull portion *301a-d* thus operates on its own exclusive Froude curve because each hull portion behaves as if it were its own hull with respect to the waterline *350*.

20 Therefore, when determining the performance characteristics of the ship *300*, each hull portion *301a-d* is analyzed individually.

[22] For example, a typical conventional ship having a length of 100 meters reaches a velocity of approximately 24 knots before reaching the hump *100* in its respective Froude curve. To overcome the hump *100* and reach a velocity corresponding to a

6

Froude number of 0.8 or greater, the ship must reach a velocity of 48 knots. Because the power required to attain a speed of 48 knots is substantial, most conventional ships are designed to cruise at a velocity below the hump *100*. The more efficient operating velocity or cruising velocity for conventional large-waterplane-area ships is at Froude numbers below 0.4.

[23]   The ship *300* of **FIG. 3**, however, is analyzed differently because each hull portion *301a-d* is exclusive and behaves independently of the other hull portions. For example, for a ship *300* with hull portions *301a-d* having lengths of 20 meters and having a frame *310* with an overall length of 100 meters, the velocity of the ship *300* at a Froude number of 0.4 is approximately 11 knots. This velocity is less than the velocity 24 knots for the conventional ship at a Froude number of 0.4. Likewise, for the ship *300* to overcome the hump *100* at a Froude number of 0.8, the ship requires a velocity of approximately 22 knots. Thus, the velocity required for the ship *300* to operate efficiently in a cruising mode at velocities above the hump *100* is far less that the velocity required for the conventional large-waterplane-area ship to operate at the same velocities.

[24]   Of course, making each hull portion *301a-d* shorter than the overall length of the frame *310* of the ship *300* leads to buoyancy problems in that the hull portions *301a-d* still need to support the weight of the typically massive frame *310*. Additional buoyancy may be provided by increasing the width or depth of each hull portion *301a-d* or by designing one or more submerged pontoons (discussed below with respect to **FIG. 5**) to be used in conjunction with the frame *310* of the ship *i.e., 300*.

[25]   The distances between hull portions *301a-d* do not substantially affect the calculation of the Froude number with respect to each hull portion. Furthermore, the

arrangement or number of hull portions *301a-d* also does not substantially affect the calculation of the Froude numbers. The arrangement, spacing, and number of hull portions *301a-d* may affect other forces such as wind resistance and water friction, but these forces are negligible compared to the force of wave drag Cw at the velocities

5   corresponding to the hump region **100**.

[26] In one embodiment, the length of each exclusive hull portion *301a-d* is varied with respect to the lengths of the other hull portions *301a-d* to avoid the simultaneous building of wave drag Cw for all the hull portions. Thus, each exclusive hull portion *301a-d* has a unique length such that no two hull portions *301a-d* reach the velocity

10   corresponding to its respective Froude number of 0.4 at the same time. In this manner, the ship overcomes several staggered humps *100* corresponding to the hump of each hull portion *301a-d* one at a time as opposed to all at once.

[27] Because the ship *300* overcomes each hump *100* at a relatively low velocity, it operates efficiently at higher Froude numbers and is not limited in velocity by the effects

15   of increased wave drag CW. This means that when cruising the ship *300* outruns its own wake and is limited in attaining higher velocities primarily by other factors such as wind resistance and water friction.

[28] FIG. 4 is another embodiment of a ship *400* having three hull portions *401a-c* that protrude from a frame *410* of the ship. Again, each hull portion *401a-c* is analyzed

20   individually with respect to a Froude number calculation, and thus the lengths of individual hull portions determine the velocities of the ship *400* required for the respective hull portions to operate at higher Froude numbers.

[29] Yet other hull designs are contemplated but not shown in drawings. For example, a ship may have several hull portions that form a figure eight pattern or an oval pattern.

8

Various other hull portion patterns are contemplated for efficiency with respect to factors other than wave drag but are not discussed herein for brevity. The number and position of hull portions can be varied to achieve desired operation characteristic of a ship including such hull portions, as will be appreciated by those skilled in the art.

5   **[30]**   **FIG. 5** is an isometric view of another ship **500** having three exclusive hull portions **501a-c** according to another embodiment of the invention. In this embodiment, the overall hull structure of the ship **500** is designed to operate in one of several operational modes. In this manner, the unique advantages of a particular type of hull, such as Catamaran or small-waterplane-area, twin hull (SWATH), can be obtained by 10   adjusting the buoyancy of the ship **500** to suit a particular operational mode.

[31]   The ship **500** includes two or more struts **510** that extend down from a main body **515** of the ship **500** and attach to one or more of the hull portions **501a-c**. The hull portions **501a-c** collectively have an adjustable buoyancy such that the draft of the ship **500** can be raised or lowered according to operating needs of the ship **500**, where 15   the draft the ship is the depth to which the boat is immersed in the water. A conventional ballasting system (not shown) can be used to adjust the buoyancy of the hull portions **501a-c** and thereby control the overall operational characteristics of the ship **500**.

[32]   For example, in a first operational mode called a Catamaran mode, the hull 20   portions **501a-c** are adjusted to their highest buoyancy. Thus, each hull portion **501a-c** behaves as if it were its own independent hull with respect to wave drag C_w as discussed above. In this mode, the ship **500** efficiently operates in the high Froude area of the respective wave drag curves of each hull portion **501a-c** because the hump **100** of

9

each hull portion is overcome at a low velocity. Again, the lengths of each hull portion *501a-c* may be varied to avoid simultaneous wave drag buildup.

[33]   In another example, the hull portions *501a-c* are adjusted to a much lower buoyancy such that the hull portions are completely submerged in water and portions of the struts *510* are also submerged. In this SWATH mode, the hull portions *501a-c* act primarily as submerged pontoons that provide a majority of the ship's buoyancy. As a result, the ship is essentially transformed from a large-waterplane-area ship to a small-waterplane-area ship to take advantage of SWATH benefits such as improved sea-keeping.

[34]   Other operational modes are contemplated and are discussed in greater detail in U.S. Patent Application No. _____, entitled VESSEL WITH A MULTI-MODE HULL, which was filed on _____, assigned to the Lockheed Missiles and Space Co. and which is incorporated by reference.

[35]   Further, the ship *500* may include any number of struts *510*, each strut *510* attached to one or more hull portion *501a-c*. For example, a ship (not shown) may have a port side strut and a starboard side strut, each strut having six individual hull portions to provide buoyancy. In another example, a ship (also not shown) may have a port side hull portion and a starboard side hull portion, each hull portion attached to the main body of the ship via a plurality of struts extending lengthwise down from the main body. In either example, the struts may be as long as the ship itself or much shorter. Likewise, the hull portions may all have the same lengths or each may have a different length, and may be arranged in various patterns as described above with respect to **FIGS. 3** and **4**.

[36] The preceding discussion is presented to enable a person skilled in the art to make and use the invention. The general principles described herein may be applied to embodiments and applications other than those detailed above without departing from the spirit and scope of the present invention. The present invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and features disclosed or suggested herein